SODERZ 5

COLD APPLIED JOINT FILLER

DESCRIPTION:

It is a bitumen-neoprene based, cold applied sealant used for horizontal and vertical joints.

USAGE AREAS:

It is used for waterproofing, filling, repairing and adherence in: The joints of walls made up of materials such as concrete, brick, gas concrete, briquette, etc.

TECHNICAL PROPERTIES:

BASE	: Bitümen-Neoprene
COLOUR	: Black
CONSISTENCY	: Thixothropic Paste
DENSITY	: 0,900 Kg/dm³
SOFTENING POINT	: >+80°C
APPLICATION TEMPERATURE	: Between +5°C and +35°C
APPLIED BY	: Trowel-Spatula
CURING TIME (20° C, 65% R.H.)	:
TOUCHING	: 45 minutes
FIRST DRYING	: 6 hours
FULL DRYING	: 72 hours

ADVANTAGES:

It can be easily applied by anyone.
It is ready to use.
As a cold applied material it does not require heating or thinning.

SURFACE PREPARATION:

The surface to be treated must be dry and clean. Do not apply onto wet, icy, greasy or dusty surfaces.

APPLICATION:

Soderz-5 is applied only onto the side exposed to water (positive insulation).
It can be applied with a trowel or spatula.
Under normal weather conditions, it starts rubberizing after 72 hours.

CONSUMPTION:

Depending on the volume of cavity to be applied, 0,900 kg/dm^3.

PACKAGING:

Net 16 kg metallic pail

SHELF LIFE - STORAGE

Shelf life is minimum 12 months when stored in dry, cool and unopened original packaging.
Do not expose to direct sunlight and heat.(S 3/15)

PRECAUTIONS:

It is flammable. Avoid smoking, lighting fire and keep away from sources of ignition (ventilator, etc.) during application (S 16).
If it is necessary to use in closed places, ventilation should be provided and health precautions should be taken (S 38-23)
Do not leave the box cover open (S 7)
Do not expose to direct sunlight or heat (S 3/15)
Keep out of reach of children (S 2)
Eyes and skin should be protected when working with all chemical substances (S 24/25)
Wear suitable gloves and protective goggles during work (S24 / 25)
Because this bulleting has been prepared considering the general conditions only, for the details except for the ones written above, please request additional written information otherwise no responsibility will be assumed due to the faults arising because of the insufficient data.
This technical bulletin invalidates the previous ones regarding this product.

EMÜLZER ASFALTEVİ TECRİT MADDELERİ SANAYİ VE TİCARET LİMİTED ŞİRKETİ
Cebeci Caddesi No 73 Küçükköy 34100 İstanbul
Telefon: +90(212)5372500 PBX – Telefaks +90(212) 6172380
www.emulzer.com.tr

FİRMAMIZ İZODER ÜYESİDİR
SUDER Su Yalıtımcıları Derneği Firmamız Suder Üyesidir
TÜRK MALI